

6 Ports 100M PoE Switch with Build-in

4*100M POE+2*FE RJ45 PoE Switch



- 4*10/100M + 2*100M RJ45 Port PoE Switch, 1-4 ports support to AF/AT;
- PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port, Maximum power: 30W/port;
- Switching capacity: 1.6Gbps, MAC table:1K;
- It is can support 1-4 support 10M/250 meters long distance transmission;
- The Power supply is 60W;
- 1 year warranty.

Introduction.

The PR-P04M series is a 10/100M unmanaged PoE switch. It has 4*10/100M PoE ports and 2*10/100M uplink RJ45 ports. Port 1-4 can support IEEE 802.3af/at standard PoE power supply, and single port PoE power reaches 30W. The maximum PoE output power is 60W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP, visual intelligent building intercom through network cable, and meet the network environment that needs high-density PoE power supply. It is suitable for hotel, campus, factory dormitory and small and medium-sized enterprises.

TECHNICAL SPECIFICATION

Model	PR-P04M
Fixed Port	4*10/100Base-TX PoE ports (Data/Power) 2*10/100Base-T Uplink RJ45 ports (Data)
POE Port	Port 1-4 support PoE
Function	The port 1-4 support 10M/250 meters long distance transmission.
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX;

	IEEE802.3ab 1000Base-T; IEEE802.3x
Ethernet Port Feature	10/100Base-T(X) 10/100/1000 Base-T automatic detection, full/half Duplex MDI/MDI-X adaptive
Fiber Port Feature	Store and Forward(Full Wire Speed)
Forwarding Mode	0.89Mpps
MAC	1K
Buffer Memory	768K
Twisted Pair Transmission	10BASE-T:Cat5 UTP(≤250 meter) 100BASE-TX:Cat5 or later UTP(≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-); Optional 4/5(+), 7/8(-)
MAX / AVERAGE Power Per Port	30W/15.4W
Total PWR / Input Voltage	65W (52VAC)
Power Consumption	Standby:<4W;Full load:<60W
LED Indicator	Power indicator: PWR (red); Network indicator : 1-4/G1-2 (green); POE indicator: PoE (red)
Power Supply	Build-in power adaptor AC100~240V 50-60Hz,65W
Operation TEMP / Humidity	-20~+55°C;5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH non condensing
Dimension	193*36*28mm
Net /Gross Weight	<0.8kg / <1.2kg
Installation Method	desktop type, wall mounted
Port lightning protection / level	Port lightning protection : 4KV 8/20us; Protection level: IP30
Certification	CCC;CE mark, commercial;CE/LVD EN60950; FCC Part 15 Class B;RoHS
Warranty	1 years, lifetime maintenance.

PACKING LIST

CONTENT	QTY	UNIT
6 Ports 100M PoE Switch with build-in (PR-P04M)	1	SET
User Guide	1	PC
Warranty Card	1	PC