

28 Ports Managed Ethernet Switch



(PR-PE24G4-M POE SWITCH)

This switch provides a network point for data transmission. All the 8 Ethernet ports can be connected with 10/100/1000Mbps quickly, and the uplink port is 1.25Gbps fiber interface. The switch features simple and reliable design, automatic identification Ethernet requirements, duplex and high-speed.

This cost-effective switch provides network layout need to simplify wireless access point (AP) and IP-based surveillance cameras network cameras in order to install in commercial network and home network. It is ideal choice for those want to deploy a small commercial network and home network that use wireless access point (AP) and IP-based surveillance cameras.

● Features

1. Can transfer data for network surveillance cameras
2. 24x 1000Mbps auto-sensing RJ45 ports, 4x 10/100/1000M Combo ports, 1 Console
3. Supports port auto-flip (Auto MDI/ MDIX)
4. Uplink port: 1.25Gbps fiber interface
6. Adopts store-and-forward architecture
7. Features with fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall mounting
8. Built-in 1U rack power supply series, easy to place it into standard mounting brackets
9. Optic fiber module is not included, can be ordered separately
10. Remote Web interface for Switch management

● Target Industries

1. HD monitor transmission and power supply
2. Wireless AP layout transmission and power supply
3. Network telephone transmission, intelligent house and home system
4. Intelligent transportation supervisory system (ITS)
5. High-speed Way supervisory/Tele-Communication System
6. Security protection system, TV medical treatment
7. Long-distance Multi-media Schooling, Campus monitoring
8. Long-distance broadcast television transmission system
9. High-building Security Protection, Military Tele-Com projects

● Technical parameter list

Hardware	
Product Name	28 Port Managed Ethernet Switch
Product Model	PR-PE24G4-M POE SWITCH
Interface	24*10/100/1000M RJ45 ports (Support POE extension) + 4 Gigabit SFP/TP Combo ports, 1 Console port
Optical	Number of interface : 4 Connector: LC by default, SC optional Wave length: Depend on SFP ports
Electrical ports	Number of interface : 28 Connector: RJ45 Rate: 10/100/1000M
Bandwidth:	56Gbps (non-blocking)
Packet Buffer Memory:	4.1M
MAC	8K
MTBF:	190,000 hours (about 21 years)
CPU	500MHZ
Switching	Store & Forward
Power Supply	AC 90~250V 50~60Hz
Transmission mode	Half/Full Duplex
Working temperature	0℃ ~50℃
Storage temperature	-40℃ ~70℃
POE ports	AF standard , each port 15.4W ,total power 400W
Software	
Network Protocols and Standards	IEEE 802.3x, IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3q , IEEE 802.3q/p, IEEE 802.1w, IEEE 802.1d , IEEE 802.1S , IEEE802.1X
VLAN	Supports port-based VLAN Supports up to 4096 VLANs Supports 802.1Q standard VLAN
Spanning tree	Support STP spanning tree protocol Supports RSTP Rapid Spanning Tree Protocol Supports MSTP Rapid Spanning Tree Protocol
Link Aggregation	Supports 8 groups of aggregation, each group supports up to 8 ports
Port mirroring	Supports both side-way port mirroring
Loop protection	Support loop protection, real-time detection, rapid alarm, precise positioning, intelligent blocking, automatic recovery
Port isolation	Support the downlink port isolation, and can communicate with the uplink port
Port flow control	Half-duplex based on back pressure control Full duplex based on PAUSE frame
Port speed limit	Supports port-based input / output bandwidth management

Multicast control	IGMPv1 / 2/3 and MLDv1 / 2 snooping
	Support GMRP registration
	Multicast address management, multicast VLAN, multicast routing port, and static multicast address
DHCP	DHCP snooping
Storm suppression	Supports unknown unicast, multicast, unknown multicast, broadcast type storm suppression Storm suppression based on bandwidth regulation and storm filtering
QOS	802.1p port queue priority algorithm Cos / Tos, QOS mark WRR (Weighted Round Robin), Weighted Priority Rotation Algorithm Support WRR, SP, WFQ three priority scheduling mode
Network management	Support WEB interface management CLI management based on Telnet and Console SNMP V1 / V2 / V3 management
Security	User port+IP address+MAC ACL based on IP and MAC Security properties of port based MAC address quantities

Ordering Information

Model No.	Description
HR-SWG202444	24x 10/100/1000M copper cable RJ45 ports(all ports support MDI/MDIX) + 4 Combo ports + 1 console port

